


Eye Foundry Hooks

A-329



- Alloy Steel - Quenched and Tempered.
- Individually Proof Tested at 2-1/2 times the Working Load Limit with certification.



A-329 Eye Foundry Hook

| Chain Size (in.) | A-329 Stock No. | Working Load Limit (lbs.)* | Weight Each (lbs.) | Dimensions (in.) | | | | | | | |
|------------------|-----------------|----------------------------|--------------------|------------------|-------|------|------|------|-------|------|------|
| | | | | B | D | I | K | L | M | N | O |
| 9/32 (1/4) | 1026179 | 3500 | 2.40 | 1.56 | 4.75 | 1.00 | 1.56 | .63 | 4.75 | 2.50 | 1.23 |
| 3/8 | 1026197 | 7100 | 4.50 | 2.00 | 5.69 | 1.27 | 1.88 | .75 | 5.75 | 3.00 | 1.50 |
| 1/2 | 1026213 | 12000 | 7.10 | 2.50 | 6.75 | 1.50 | 2.22 | 1.00 | 6.88 | 3.50 | 1.75 |
| 5/8 | 1026231 | 18100 | 12.20 | 3.00 | 7.81 | 1.81 | 2.63 | 1.25 | 8.06 | 4.00 | 2.03 |
| 3/4 | 1026259 | 28300 | 19.30 | 3.50 | 9.13 | 2.20 | 3.50 | 1.50 | 9.25 | 4.50 | 2.56 |
| 7/8 | 1026277 | 34200 | 26.30 | 4.00 | 10.06 | 2.25 | 3.38 | 1.75 | 10.38 | 5.00 | 2.78 |

* Ultimate Load is 4 times the Working Load Limit.

