

Shank Hooks


**SEE APPLICATION AND
WARNING INFORMATION**

 Para Español: www.thecrosbygroup.com On Pages 122 - 123

S-319 / S-319N



- The most complete line of shank hoist hooks. Available 3/4 to 300 metric tons.
- Hook Identification code forged into each hook.
- Quenched and Tempered.
- Available in carbon steel, alloy steel, and bronze.
- Proper design, careful forging, and precision controlled quench and tempering give maximum strength without excessive weight and bulk.
- Every Crosby Shank Hook has a pre-drilled cam which can be equipped with a latch. Simply purchase the latch assemblies listed and shown on pages 101 - 103. Even years after purchase of the original hook, latch assemblies can be added.
- Type Approval and certification in accordance with ABS 2006 Steel Vessel Rules 1-1-17.7, and ABS Guide for Certification of Cranes.

Patented trademark indicates
QUIC-CHECK® product.

Hook Material Codes: A-Alloy Steel,
B-Bronze High Strength,
C-Carbon Steel.

Working Load Limit (t) [*]			Hook ID Code	Shank Hooks Stock No.			Shank Length ‡	Weight Each (lbs.)	Rep. Latch Kits		
Carbon	Alloy	Bronze		Carbon S-319C S-319CN	Alloy S-319A S-319AN	Bronze S-319BN			S-4320 Stock No.	PL Stock No.	SS-4055 Stock No.
3/4	1	.5	†D	1028505	1028701	1028900	Std.	.50	1096325	-	-
1	1.5	.6	†F	1028514	1028710	1028909	Std.	.75	1096374	-	-
1-1/2	2	1	†G	1028523	1028723	1028918	Std.	1.00	1096421	-	-
2	3	1.4	†H	1028532	1028732	1028927	Std.	1.82	1096468	-	-
3	5	2	†I	1028541	1028741	1028936	Std.	3.69	1096515	1092000	-
5	7	3.5	†J	1028550	1028750	1028945	Std.	7.25	1096562	1092001	-
7-1/2	11	5	†K	1028563	1028765	1028954	Std.	13.49	1096609	1092002	-
10	15	6.5	†L	1028572	1028774	1028963	Std.	18.00	1096657	1092003	-
15	22	10	†N	1028581	1028783	1028972	Std.	35.33	1096704	1092004	-
20	30	-	O	1024386	1024803	-	Std.	72.00	-	1093716	1090161
20	30	-	O	1024402	1024821	-	Long	85.50	-	1093716	1090161
25	37	-	P	1024420	1024849	-	Std.	134.00	-	1093717	1090189
25	37	-	P	1024448	1024867	-	Long	172.00	-	1093717	1090189
30	45	-	S	1024466	1024885	-	Std.	182.00	-	1093718	1090189
30	45	-	S	1024484	1024901	-	Long	214.00	-	1093718	1090189
40	60	-	T	1024509	1024929	-	Std.	268.00	-	1093719	1090205
40	60	-	T	1024545	1024965	-	Long	312.00	-	1093719	1090205
50	75	-	U	1024563	1024983	-	Std.	390.00	-	1093720	-
50	75	-	U	1024581	1025009	-	Long	426.00	-	1093720	-
-	100	-	W	-	1025027	-	Std.	610.00	-	1093721	-
-	100	-	W	-	1025045	-	Long	675.00	-	1093721	-
-	150	-	X	-	1025063	-	Std.	735.00	-	1093721	-
-	200	-	Y	-	1025081	-	Std.	1020.00	-	1093723	-
-	300	-	Z	-	1025090	-	Std.	1390.00	-	1093724	-

* NOTE: Proof load is 2 times Working Load Limit.
 All carbon hooks designed with a 5/1 safety factor.
 All alloy hooks 1-22t designed with a 4.5/1 safety factor.
 All alloy hooks 30t and larger designed with a 4/1 safety factor.
 All bronze hooks designed with a 4/1 safety factor.

† New 319N style hook.

‡ See column "Y" on following page for actual length.

