


Weldless Sling Links

G-341 / S-341

- Forged carbon steel - Quenched and Tempered.
- Self Colored or Hot Dip galvanized.



G-341 / S-341 Weldless Sling Links

Size (A) (in.)	Stock No.		Working Load Limit Single Pull (lbs.)*	Weight Each (lbs.)	Dimensions (in.)				
	G-341 Galv.	S-341 S.C.			B	C	D	E	F
3/8	1013897	1013904	1800	.23	1.13	.75	3.00	2.25	.38
1/2	1013913	1013922	2900	.55	1.50	1.00	4.00	3.00	.50
5/8	1013931	1013940	4200	1.06	1.87	1.25	5.00	3.75	.63
3/4	1013959	1013968	6000	1.88	2.25	1.50	6.00	4.50	.75
7/8	1013977	1013986	8300	2.75	2.63	1.75	7.00	5.25	.88
1	1013995	1014002	10800	4.35	3.00	2.00	8.00	6.00	1.00
1 1/4	1014011	1014020	16750	7.60	4.00	2.50	10.25	7.50	1.25
1 3/8	1014039	1014048	20500	11.30	4.13	2.75	11.00	8.25	1.38

* Ultimate Load is 6 times the Working Load Limit. Based on single leg sling (in-line load), or resultant load on multiple legs with an included angle less than or equal to 120°.