Mill Valley Splicing, Inc. | Belchertown, MA 01007 | Phone: 413-323-6307 | Email: info@millvalleysplicing.com


## Web/Chain Connector

## S-282 WEB / CHAIN CONNECTOR



Designed around the same concept as our S-280 Web Connector, the S-282 Chain Connector makes the connection from your web sling to existing chain quick and easy.

- · Available in three sizes:
  - 3-1/4 ton Working Load Limit -2" Webbing to 3/8" (10mm) chain.
  - 4-1/2 ton Working Load Limit 1-1/2" (3" Tapered Webbing) to 1/2" (13mm) chain.
  - 6-1/4 ton Working Load Limit 2" (4" Tapered Webbing) to 5/8" (16mm) chain.
- · Alloy Steel (Quenched and Tempered)
- Each Connector has a Product Identification Code (PIC) for material traceability along with a Working Load Limit and the name Crosby forged into it.
- Uses same spool and cover as S-280 Web Connector.
  - Replacement Kit for Spool and Web Cover available.



## S-282 Web / Chain Connector

Round	Web Slings*				Working			Dimensions (in.)			
Sling Size (No.)	Webbing Width (in.)	Eye Width (in.)	Ply	Chain Size	Load Limit (Tons) †	S-282 Stock No.	Weight Each (lbs.)	В	C	E	F
1 & 2	2	2	2	3/8	3-1/4	1021084	1.9	4.33	2.13	2.11	4.77
3	3	1.5	2	1/2	4-1/2	1021093	2.8	5.04	1.63	2.44	4.54
4	4	2	2	5/8	6-1/4	1021100	4.3	5.69	2.13	2.54	5.31

NOTE: Designed for use with Type III, (Eye & Eye), Class 7, 2 Ply web slings.
† Maximum Proof Load is 2-1/2 times the Working Load Limit. Minimum Ultimate Strength is 4 times the Working Load Limit.

