



# Mechanical Splice Sling

## Two Leg Bridle

6x19 and 6x37 Classification – IWRC

Rated Capacity in Tons of 2,000 lb.



Rope Diameter (Inches)	60°		45°		30°		EYE SIZE (Inches)	
	IP	EIP	IP	EIP	IP	EIP	A	B
1/4	.97	1.1	.79	.91	.56	.65	3	6
5/16	1.5	1.7	1.2	1.4	.87	1.0	3	6
3/8	2.2	2.5	1.8	2.0	1.2	1.4	3	6
7/16	2.9	3.4	2.4	2.7	1.7	1.9	4	8
1/2	3.8	4.4	3.1	3.6	2.2	2.5	4	8
9/16	4.8	5.5	3.9	4.5	2.8	3.2	4	8
5/8	5.9	6.8	4.8	5.5	3.4	3.9	5	10
3/4	8.4	9.7	6.9	7.9	4.9	5.6	6	12
7/8	11	13	9.3	11	6.6	7.6	7	14
1	15	17	12	14	8.5	9.8	8	16
1-1/8	18	21	15	17	10	12	9	18
1-1/4	22	26	18	21	13	15	10	20
1-3/8	27	31	22	25	15	18	11	22
1-1/2	32	37	26	30	18	21	12	24
1-5/8	37	42	30	35	21	24	-	-
1-3/4	43	49	35	40	25	28	14	28
1-7/8	49	56	40	46	28	32	-	-
2	55	63	45	52	32	37	16	32
2-1/4	67	77	55	63	39	44	18	36
2-1/2	82	94	67	77	47	54	20	40
2-3/4	98	113	80	92	57	65	24	48
3	115	133	94	108	67	77	27	54

End options:

MSS\_Loop

MSS\_Sloop

MSS\_Hook

MSS\_Sling

